

Perfect seedbeds begin with the All-New Frontier Mulch Finisher

Announcing the new 12 Series Mulch Finisher, the latest tillage tool from Frontier Equipment – from tilling hard, layered soil to preparing existing food plots for reseeding, the 12 Series Mulch Finisher is designed for versatility and performance.

Choose from the MF1204, MF1206 and MF1208 – ideal for tractors from 30 to 100 horsepower. The 12 Series Mulch Finishers come with 6, 8, or 12 disk blades for excellent residue management. These productive tillage tools are also equipped with vibrating S-tines that help you achieve uniform tillage depth using one of **three distinct ground management options**.

Chisel Spikes till and break up compacted soil. And because the spikes pull through soil with less draft, you'll conserve fuel over each pass, reducing costs. Reversible tips give your spikes longer life.

Turning Tips offer greater ground penetration through heavy residue, grass, or tough ground cover. Turning Tips break up soil compaction while turning over soil to bury residue.

9-inch Sweeps lift the soil and spread it evenly for a smooth, level seedbed.

The Frontier Mulch Finishers are sold and supported by John Deere dealers. To help you select the right model of Frontier Mulch Finisher, talk to your local John Deere dealer, your exclusive source of Frontier Equipment.

www.BuyFrontier.com



Chisel Spikes



Turning Tips



9-inch Sweeps

Working Widths of 4, 6, and 8 Feet

All-New Frontier 12 Series Mulch Finisher

Expect a smoother, better seedbed every time.

DETAILS

As an extra benefit, a pull-type conversion kit is offered as a field-installed attachment for your ATV or utility vehicle.



As an additional option, attach the Rolling Basket (above) to the Frontier Mulch Finisher to till, condition, and level...all in a single pass! Get a smooth planting-ready seedbed each time. The efficiency saves time and money in your operations with increased planting productivity.

SPECIFICATIONS

Model	MF1204	MF1206	MF1208
Machine Weight	753 lbs 803 lbs with pull-type hitch	1066 lbs	1242 lbs
Tractor Horsepower Range	30-50	45-75	60-100
Single Point Hitch (Optional) Horsepower Range	20 (500 CC) -40	NA	NA
Working Width	42"	60"	82"
Unit Length	53"	74"	74"
Unit Height	35"	35"	35"
Number of Blades	6	8	12
Blade Diameter	16"	18"	18"
Blade Thickness	3 mm	3.5 mm	3.5 mm
Blade Spacing	8.25"	7.50"	7.50"
Blade Type	Notched	Notched	Notched
Bearing Hanger	.375" Formed Plate With Reinforcement, 2 each .625 U-bolts per hanger	.375" Formed Plate With Reinforcement, 2 each .625 U-bolts per hanger	.375" Formed Plate With Reinforcement, 2 each .625 U-bolts per hanger
Bearing Type	1" Square Sealed Bearing	1" Square Sealed Bearing	1" Square Sealed Bearing
Gang Axle	1" Square	1" Square	1" Square
Gang Adjustment	Pinned Adjustment	Pinned Adjustment	Pinned Adjustment
3 Point Hitch Type	Cat. 1	Cat. 1/2	Cat. 1/2
iMatch™ Compatible	Yes	Yes	Yes
Pull-Type Hitch (Optional)	Yes	No	No
Number of S-Tines	3	7	9
1.75" Reversible Chisel Point	3	7	9
9" Sweep	3	7	9
Right Turning Point	1	3	4
Left Turning Point	1	3	4
Approximate Set-up Time (Man hours)	1	1	1



This literature has been compiled for worldwide circulation. While general information, pictures and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL JOHN DEERE DEALER FOR DETAILS. Frontier Equipment reserves the right to change specifications, design and price of products described in this literature without notice. Copyright 2008, Frontier Equipment.

www.BuyFrontier.com